

52. IWK

Internationales Wissenschaftliches Kolloquium
International Scientific Colloquium



PROCEEDINGS

| 10 - 13 September 2007

FACULTY OF COMPUTER SCIENCE AND AUTOMATION



COMPUTER SCIENCE MEETS AUTOMATION

VOLUME II

Session 6 - Environmental Systems: Management and Optimisation

**Session 7 - New Methods and Technologies for Medicine and
Biology**

Session 8 - Embedded System Design and Application

Session 9 - Image Processing, Image Analysis and Computer Vision

Session 10 - Mobile Communications

Session 11 - Education in Computer Science and Automation

Bibliografische Information der Deutschen Bibliothek

Die Deutsche Bibliothek verzeichnet diese Publikation in der deutschen Nationalbibliografie; detaillierte bibliografische Daten sind im Internet über <http://dnb.ddb.de> abrufbar.

ISBN 978-3-939473-17-6

Impressum

- Herausgeber: Der Rektor der Technischen Universität Ilmenau
Univ.-Prof. Dr. rer. nat. habil. Peter Scharff
- Redaktion: Referat Marketing und Studentische Angelegenheiten
Kongressorganisation
Andrea Schneider
Tel.: +49 3677 69-2520
Fax: +49 3677 69-1743
e-mail: kongressorganisation@tu-ilmenau.de
- Redaktionsschluss: Juli 2007
- Verlag: 
Technische Universität Ilmenau/Universitätsbibliothek
Universitätsverlag Ilmenau
Postfach 10 05 65
98684 Ilmenau
www.tu-ilmenau.de/universitaetsverlag
- Herstellung und Auslieferung: Verlagshaus Monsenstein und Vannerdat OHG
Am Hawerkamp 31
48155 Münster
www.mv-verlag.de
- Layout Cover: www.cey-x.de
- Bezugsmöglichkeiten: Universitätsbibliothek der TU Ilmenau
Tel.: +49 3677 69-4615
Fax: +49 3677 69-4602

© Technische Universität Ilmenau (Thür.) 2007

Diese Publikationen und alle in ihr enthaltenen Beiträge und Abbildungen sind urheberrechtlich geschützt. Mit Ausnahme der gesetzlich zugelassenen Fälle ist eine Verwertung ohne Einwilligung der Redaktion strafbar.

Preface

Dear Participants,

Confronted with the ever-increasing complexity of technical processes and the growing demands on their efficiency, security and flexibility, the scientific world needs to establish new methods of engineering design and new methods of systems operation. The factors likely to affect the design of the smart systems of the future will doubtless include the following:

- As computational costs decrease, it will be possible to apply more complex algorithms, even in real time. These algorithms will take into account system nonlinearities or provide online optimisation of the system's performance.
- New fields of application will be addressed. Interest is now being expressed, beyond that in "classical" technical systems and processes, in environmental systems or medical and bioengineering applications.
- The boundaries between software and hardware design are being eroded. New design methods will include co-design of software and hardware and even of sensor and actuator components.
- Automation will not only replace human operators but will assist, support and supervise humans so that their work is safe and even more effective.
- Networked systems or swarms will be crucial, requiring improvement of the communication within them and study of how their behaviour can be made globally consistent.
- The issues of security and safety, not only during the operation of systems but also in the course of their design, will continue to increase in importance.

The title "Computer Science meets Automation", borne by the 52nd International Scientific Colloquium (IWK) at the Technische Universität Ilmenau, Germany, expresses the desire of scientists and engineers to rise to these challenges, cooperating closely on innovative methods in the two disciplines of computer science and automation.

The IWK has a long tradition going back as far as 1953. In the years before 1989, a major function of the colloquium was to bring together scientists from both sides of the Iron Curtain. Naturally, bonds were also deepened between the countries from the East. Today, the objective of the colloquium is still to bring researchers together. They come from the eastern and western member states of the European Union, and, indeed, from all over the world. All who wish to share their ideas on the points where "Computer Science meets Automation" are addressed by this colloquium at the Technische Universität Ilmenau.

All the University's Faculties have joined forces to ensure that nothing is left out. Control engineering, information science, cybernetics, communication technology and systems engineering – for all of these and their applications (ranging from biological systems to heavy engineering), the issues are being covered.

Together with all the organizers I should like to thank you for your contributions to the conference, ensuring, as they do, a most interesting colloquium programme of an interdisciplinary nature.

I am looking forward to an inspiring colloquium. It promises to be a fine platform for you to present your research, to address new concepts and to meet colleagues in Ilmenau.



Professor Peter Scharff
Rector, TU Ilmenau



Professor Christoph Ament
Head of Organisation

CONTENTS

	Page
6 Environmental Systems: Management and Optimisation	
T. Bernard, H. Linke, O. Krol A Concept for the long term Optimization of regional Water Supply Systems as a Module of a Decision Support System	3
S. Röhl, S. Hopfgarten, P. Li A groundwater model for the area Darkhan in Kharaa river Th. Bernard, H. Linke, O. Krol basin	11
A. Khatanbaatar Altantuul The need designing integrated urban water management in cities of Mongolia	17
T. Rauschenbach, T. Pfützenreuter, Z. Tong Model based water allocation decision support system for Beijing	23
T. Pfützenreuter, T. Rauschenbach Surface Water Modelling with the Simulation Library ILM-River	29
D. Karimanzira, M. Jacobi Modelling yearly residential water demand using neural networks	35
Th. Westerhoff, B. Scharaw Model based management of the drinking water supply system of city Darkhan in Mongolia	41
N. Buyankhishig, N. Batsukh Pumping well optimi ation in the Shivee-Ovoo coal mine Mongolia	47
S. Holzmüller-Laue, B. Göde, K. Rimane, N. Stoll Data Management for Automated Life Science Applications	51
N. B. Chang, A. Gonzalez A Decision Support System for Sensor Deployment in Water Distribution Systems for Improving the Infrastructure Safety	57
P. Hamolka, I. Vrublevsky, V. Parkoun, V. Sokol New Film Temperature And Moisture Microsensors for Environmental Control Systems	63
N. Buyankhishig, M. Masumoto, M. Aley Parameter estimation of an unconfined aquifer of the Tuul River basin Mongolia	67

M. Jacobi, D. Karimanzira	73
Demand Forecasting of Water Usage based on Kalman Filtering	

7 New Methods and Technologies for Medicine and Biology

J. Meier, R. Bock, L. G. Nyúl, G. Michelson	81
Eye Fundus Image Processing System for Automated Glaucoma Classification	
L. Hellrung, M. Trost	85
Automatic focus depending on an image processing algorithm for a non mydriatic fundus camera	
M. Hamsch, C. H. Igney, M. Vauhkonen	91
A Magnetic Induction Tomography System for Stroke Classification and Diagnosis	
T. Neumuth, A. Pretschner, O. Burgert	97
Surgical Workflow Monitoring with Generic Data Interfaces	
M. Pfaff, D. Woetzel, D. Driesch, S. Toepfer, R. Huber, D. Pohlers, D. Koczan, H.-J. Thiesen, R. Guthke, R. W. Kinne	103
Gene Expression Based Classification of Rheumatoid Arthritis and Osteoarthritis Patients using Fuzzy Cluster and Rule Based Method	
S. Toepfer, S. Zellmer, D. Driesch, D. Woetzel, R. Guthke, R. Gebhardt, M. Pfaff	107
A 2-Compartment Model of Glutamine and Ammonia Metabolism in Liver Tissue	
J. C. Ferreira, A. A. Fernandes, A. D. Santos	113
Modelling and Rapid Prototyping an Innovative Ankle-Foot Orthosis to Correct Children Gait Pathology	
H. T. Shandiz, E. Zahedi	119
Noninvasive Method in Diabetic Detection by Analyzing PPG Signals	
S. V. Drobot, I. S. Asayenok, E. N. Zacepin, T. F. Sergiyenko, A. I. Svirnovskiy	123
Effects of Mm-Wave Electromagnetic Radiation on Sensitivity of Human Lymphocytes to Ionizing Radiation and Chemical Agents in Vitro	

8 Embedded System Design and Application

B. Däne	131
Modeling and Realization of DMA Based Serial Communication for a Multi Processor System	

M. Müller, A. Pacholik, W. Fengler Tool Support for Formal System Verification	137
A. Pretschner, J. Alder, Ch. Meissner A Contribution to the Design of Embedded Control Systems	143
R. Ubar, G. Jervan, J. Raik, M. Jenihhin, P. Ellervee Dependability Evaluation in Fault Tolerant Systems with High-Level Decision Diagrams	147
A. Jutmann On LFSR Polynomial Calculation for Test Time Reduction	153
M. Rosenberger, M. J. Schaub, S. C. N. Töpfer, G. Linß Investigation of Efficient Strain Measurement at Smallest Areas Applying the Time to Digital (TDC) Principle	159
 9 Image Processing, Image Analysis and Computer Vision	
J. Meyer, R. Espiritu, J. Earthman Virtual Bone Density Measurement for Dental Implants	167
F. Erfurth, W.-D. Schmidt, B. Nyuyki, A. Scheibe, P. Saluz, D. Faßler Spectral Imaging Technology for Microarray Scanners	173
T. Langner, D. Kollhoff Farbbasierte Druckbildinspektion an Rundkörpern	179
C. Lucht, F. Gaßmann, R. Jahn Inline-Fehlerdetektion auf freigeformten, texturierten Oberflächen im Produktionsprozess	185
H.-W. Lahmann, M. Stöckmann Optical Inspection of Cutting Tools by means of 2D- and 3D-Imaging Processing	191
A. Melitzki, G. Stanke, F. Weckend Bestimmung von Raumpositionen durch Kombination von 2D-Bildverarbeitung und Mehrfachlinienlasertriangulation - am Beispiel von PKW-Stabilisatoren	197
F. Boochs, Ch. Raab, R. Schütze, J. Traiser, H. Wirth 3D contour detection by means of a multi camera system	203

M. Brandner Vision-Based Surface Inspection of Aeronautic Parts using Active Stereo	209
H. Lettenbauer, D. Weiss X-ray image acquisition, processing and evaluation for CT-based dimensional metrology	215
K. Sickel, V. Daum, J. Hornegger Shortest Path Search with Constraints on Surface Models of In-the-ear Hearing Aids	221
S. Husung, G. Höhne, C. Weber Efficient Use of Stereoscopic Projection for the Interactive Visualisation of Technical Products and Processes	227
N. Schuster Measurement with subpixel-accuracy: Requirements and reality	233
P. Brückner, S. C. N. Töpfer, M. Correns, J. Schnee Position- and colour-accurate probing of edges in colour images with subpixel resolution	239
E. Sparrer, T. Machleidt, R. Nestler, K.-H. Franke, M. Niebelschütz Deconvolution of atomic force microscopy data in a special measurement mode – methods and practice	245
T. Machleidt, D. Kapusi, T. Langner, K.-H. Franke Application of nonlinear equalization for characterizing AFM tip shape	251
D. Kapusi, T. Machleidt, R. Jahn, K.-H. Franke Measuring large areas by white light interferometry at the nanopositioning and nanomeasuring machine (NPM)M)	257
R. Burdick, T. Lorenz, K. Bobey Characteristics of High Power LEDs and one example application in with-light-interferometry	263
T. Koch, K.-H. Franke Aspekte der strukturbasierten Fusion multimodaler Satellitendaten und der Segmentierung fusionierter Bilder	269
T. Riedel, C. Thiel, C. Schmallius A reliable and transferable classification approach towards operational land cover mapping combining optical and SAR data	275
B. Waske, V. Heinzl, M. Braun, G. Menz Classification of SAR and Multispectral Imagery using Support Vector Machines	281

V. Heinzl, J. Franke, G. Menz Assessment of differences in multisensoral remote sensing imageries caused by discrepancies in the relative spectral response functions	287
I. Aksit, K. Bünger, A. Fassbender, D. Frekers, Chr. Götze, J. Kemenas An ultra-fast on-line microscopic optical quality assurance concept for small structures in an environment of man production	293
D. Hofmann, G. Linss Application of Innovative Image Sensors for Quality Control	297
A. Jablonski, K. Kohrt, M. Böhm Automatic quality grading of raw leather hides	303
M. Rosenberger, M. Schellhorn, P. Brückner, G. Linß Uncompressed digital image data transfer for measurement techniques using a two wire signal line	309
R. Blaschek, B. Meffert Feature point matching for stereo image processing using nonlinear filters	315
A. Mitsiukhin, V. Pachynin, E. Petrovskaya Hartley Discrete Transform Image Coding	321
S. Hellbach, B. Lau, J. P. Eggert, E. Körner, H.-M. Groß Multi-Cue Motion Segmentation	327
R. R. Alavi, K. Brieß Image Processing Algorithms for Using a Moon Camera as Secondary Sensor for a Satellite Attitude Control System	333
S. Bauer, T. Döring, F. Meysel, R. Reulke Traffic Surveillance using Video Image Detection Systems	341
M. A-Megeed Salem, B. Meffert Wavelet-based Image Segmentation for Traffic Monitoring Systems	347
E. Einhorn, C. Schröter, H.-J. Böhme, H.-M. Groß A Hybrid Kalman Filter Based Algorithm for Real-time Visual Obstacle Detection	353
U. Knauer, R. Stein, B. Meffert Detection of opened honeybee brood cells at an early stage	359

10 Mobile Communications

K. Ghanem, N. Zamin-Khan, M. A. A. Kalil, A. Mitschele-Thiel Dynamic Reconfiguration for Distributing the Traffic Load in the Mobile Networks	367
N. Z.-Khan, M. A. A. Kalil, K. Ghanem, A. Mitschele-Thiel Generic Autonomic Architecture for Self-Management in Future Heterogeneous Networks	373
N. Z.-Khan, K. Ghanem, St. Leistritz, F. Liers, M. A. A. Kalil, H. Kärst, R. Böringer Network Management of Future Access Networks	379
St. Schmidt, H. Kärst, A. Mitschele-Thiel Towards cost-effective Area-wide Wi-Fi Provisioning	385
A. Yousef, M. A. A. Kalil A New Algorithm for an Efficient Stateful Address Autoconfiguration Protocol in Ad hoc Networks	391
M. A. A. Kalil, N. Zamin-Khan, H. Al-Mahdi, A. Mitschele-Thiel Evaluation and Improvement of Queueing Management Schemes in Multihop Ad hoc Networks	397
M. Ritzmann Scientific visualisation on mobile devices with limited resources	403
R. Brecht, A. Kraus, H. Krömker Entwicklung von Produktionsrichtlinien von Sport-Live-Berichterstattung für Mobile TV Übertragungen	409
N. A. Tam RCS-M: A Rate Control Scheme to Transport Multimedia Traffic over Satellite Links	421
Ch. Kellner, A. Mitschele-Thiel, A. Diab Performance Evaluation of MIFA, HMIP and HAWAII	427
A. Diab, A. Mitschele-Thiel MIFAv6: A Fast and Smooth Mobility Protocol for IPv6	433
A. Diab, A. Mitschele-Thiel CAMP: A New Tool to Analyse Mobility Management Protocols	439

11 Education in Computer Science and Automation

S. Bräunig, H.-U. Seidel Learning Signal and Pattern Recognition with Virtual Instruments	447
St. Lambeck Use of Rapid-Control-Prototyping Methods for the control of a nonlinear MIMO-System	453
R. Pittschellis Automatisierungstechnische Ausbildung an Gymnasien	459
A. Diab, H.-D. Wuttke, K. Henke, A. Mitschele-Thiel, M. Ruhwedel MAeLE: A Metadata-Driven Adaptive e-Learning Environment	465
V. Zöppig, O. Radler, M. Beier, T. Ströhla Modular smart systems for motion control teaching	471
N. Pranke, K. Froitzheim The Media Internet Streaming Toolbox	477
A. Fleischer, R. Andreev, Y. Pavlov, V. Terzieva An Approach to Personalized Learning: A Technique of Estimation of Learners Preferences	485
N. Tsyrelchuk, E. Ruchaevskaia Innovational pedagogical technologies and the Information educational medium in the training of the specialists	491
Ch. Noack, S. Schwintek, Ch. Ament Design of a modular mechanical demonstration system for control engineering lectures	497

Susanne Toepfer, Sebastian Zellmer, Dominik Driesch, Dirk Woetzel,
Reinhard Guthke, Rolf Gebhardt, Michael Pfaff

A 2-Compartment Model of Glutamine and Ammonia Metabolism in Liver Tissue

7 NEW METHODS AND TECHNOLOGIES FOR MEDICINE AND BIOLOGY

Introduction

The aim of this modelling study was to develop an adequate model of glutamine and ammonia metabolism in perfused rat livers under particular consideration of the metabolic zonation in the liver lobulus.

The liver is the main organ of intermediary metabolism. It consists of thousands of identical small sub-units, the liver lobuli. Each lobulus consists of a central vein and is confined by portal fields in a hexagonal arrangement. From each portal field, the blood flows into the lobulus and is drained through the central vein. The area surrounding the portal field is called the periportal region and the area around the central vein is called the perivenous region. During passage from the portal field to the central vein, blood passes a number of hepatocytes. Hepatocytes realize almost all metabolic functions, e.g. synthesis and degradation of amino acids, proteins, lipids and carbohydrates [1]. Due to highly regulated enzyme expression [2], most metabolic pathways are only present either in the periportal or the perivenous compartment of the lobulus. This is called metabolic zonation. As a consequence, synthesis and degradation are simultaneously carried out but in different compartments of the lobuli. One example where this metabolic zonation has an important impact is glutamine and ammonia metabolism. In the organism toxic ammonia is removed by converting glutamate into glutamine. The glutamine-rich blood enters the liver at the periportal region and the enzyme glutaminase (G) degrades glutamine to ammonia and glutamate. Subsequently, toxic ammonia is eliminated by the enzyme carbamoyl-phosphate synthetase (C) in the course of urea synthesis [1, 3]. Remaining ammonia is detoxified in periportal hepatocytes by converting glutamate into glutamine by the glutamine synthetase (GS).

Experimental Data

The model identification presented here is based on experimental data published in [3]. In [3], the metabolic zonation was investigated in perfused rat livers by comparing metabolic flux rates depending on the perfusion direction. The isolated rat livers were perfused without recirculation either in physiological antegrade (from portal to central vein) or in retrograde (from central to portal vein) direction with a weight-specific constant perfusion flow F_{mL} . For several experiments, either glutamine synthetase or carbamoyl-phosphate synthetase were inhibited by addition of methionine sulfoximine to the perfusion fluid or by using a bicarbonate-free buffer, respectively. Modelling is based on measured glutamine (GLN), ammonia (NH₄), urea (UREA) and glutamate (GLU) concentrations in the influent and effluent of the perfused rat livers recorded from 16 perfusion experiments (Fig. 2, blue bars). All data were obtained in metabolic steady-state and are means from 4-12 separate runs. Data preprocessing was performed by scaling measured effluent concentrations in order to guarantee that the overall sum of nitrogen in the influent together with the estimated endogenously arising nitrogen is equal to the overall sum of nitrogen in the effluent.

Knowledge- and Data-driven Modelling

Model development comprises the knowledge-driven determination of the model structure and the subsequent data-driven estimation of the model parameters.

The model consists of eight differential equations with one equation for each concentration $c_{GLN,i}$, $c_{NH_4,i}$, $c_{UREA,i}$, $c_{GLU,i}$ and for each compartment ($i = 1,2$), respectively. Both compartments are run through by the perfusion flow F carrying the concentrations $c_{j,Input}$ in influent ($j = GLN, NH_4, UREA, GLU$). During antegrade perfusion, the effluent concentrations $c_{j,Output}$ are equal to the concentrations $c_{j,2}$ in compartment 2 (Fig. 1), while during retrograde perfusion, they are equal to the concentrations $c_{j,1}$ in compartment 1 (not shown).

The periportal compartment 1 with the volume V_1 includes glutamine degradation by glutaminase and urea synthesis by carbamoyl-phosphate synthetase. In contrast, the perivenous compartment 2 with the volume V_2 contains glutamine synthesis by the enzyme glutamine synthetase (Fig. 1). The corresponding reaction equations consider stimulation (Michaelis-Menten equation with Michaelis-Menten constant K_M) and inhibition (noncompetitive inhibition with dissoziation constant K_i) by substrates and


products. Thus, glutamine degradation v_G has a maximum velocity $v_{MAX,G}$ and is stimulated by glutamine ($K_{M,G,GLN}$) and portal ammonium ions ($K_{M,G,NH4}$) [3, 4]. Urea synthesis v_C is characterized by the maximum velocity $v_{MAX,C}$ and the stimulation by ammonia ($K_{M,C,NH4}$). Glutamine synthesis v_{GS} has the maximum velocity $v_{MAX,GS}$ and is stimulated by ammonia ($K_{M,GS,NH4}$) and glutamate ($K_{M,GS,GLU}$). Furthermore, it is inhibited by the product glutamine ($K_{I,GS,GLN}$) [4]. Consequently, each differential equation can consist of three parts. The first part describes concentration changes caused by synthesis and degradation from the three metabolic reactions (G,C,GS) that were taken into account. The both other parts describe the change of concentrations caused by the inflow and the outflow of the perfusion stream F .

Endogenous ammonia arises from endogenous protein and amino acid breakdown [5]. Endogenous ammonia production is located mainly in the periportal compartment, which consists of more than 95 % of all hepatocytes of the glutamine/NH₄ system. Modelling the observed effects caused by endogenous ammonia requires two positions where the endogenous ammonia portions $c_{NH4,Endog1}$ and $c_{NH4,Endog2}$ operate. Furthermore, several experiments point to an endogenous source of glutamate $c_{GLU,Endog}$ in the perivenous compartment 2 (Fig. 1).

During experiments with inhibition of glutamine synthesis or urea synthesis, the respective metabolic reactions are only active to a very small degree. In order to model this effect, the synthesis rates v_{GS} and v_C are multiplied with the additional activity factors e_{GS} and e_C . During the simulation of experiments without inhibition, these factors are set to one and, thus, have no influence on the synthesis rates. In case of simulating experiments with inhibition, the activity factors possess values much smaller than one and, therefore, decrease the synthesis rates.

A common model for all 16 experiments was identified. The parameters of the model were estimated by one of the following methods: (i) Parameters are known or can be calculated from known experimental settings. (ii) Parameters can be directly calculated from the measurement data. (iii) Parameters are optimized by fitting the model output to the measurement data using a nonlinear optimization technique.

The first method is applied for the yield coefficients Y and the terms F/V_i that are constant for all experiments due to the weight-specific perfusion flow F_{mL} . The second method is used to estimate the total levels of endogenous ammonia and glutamate. All remaining model parameters are optimized by minimizing the root square error (RSE)



$$v_G = v_{MAX,G} \cdot c_{GLN,1} / (K_{M,G,GLN} + c_{GLN,1}) \cdot c_{NH4,Input} / (K_{M,G,NH4} + c_{NH4,Input})$$

$$v_C = v_{MAX,C} \cdot c_{NH4,1} / (K_{M,C,NH4} + c_{NH4,1})$$

$$v_{GS} = v_{MAX,GS} \cdot c_{NH4,2} / (K_{M,GS,NH4} + c_{NH4,2}) \cdot c_{GLU,2} / (K_{M,GS,GLU} + c_{GLU,2}) \cdot K_{i,GS,GLN} / (K_{i,GS,GLN} + c_{GLN,2})$$

Fig. 1: Structure of the 2-compartment liver model (antegrade perfusion)

between the measured and preprocessed concentrations c_j^k and the simulated model output $c_{j,Output}^k$ for experiments k ($k = 1, \dots, 16$ and $j = \text{GLN, NH4, UREA}$).

It should be mentioned, that the model output $c_{GLU,Output}$ can not be adapted with an acceptable quality to the measured glutamate concentrations. It is assumed, that in contrast to the GLN, NH4 and UREA release, the glutamate level is strongly influenced by other pathways not taken into account here. However, the model can simulate the effects of the three considered metabolic reactions on the release of glutamate.

Results

The modelling results are shown in Fig. 2. The 2-compartment model developed is able to cover all main effects with respect to glutamine, ammonia and urea release observed during the experiments with changing perfusion direction. The following effects are described in [3] and are captured by the model:




Fig 2: Results of the 2-compartment model (RSE = 0.356); blue = measurement data, red = model output, gray = model output, but no measurement data available

- Ammonium ions can be very efficiently eliminated during antegrade perfusion but are released by the liver to a considerable extend during retrograde perfusion (Exp. 1 and 2, Exp. 7 and 8 in Fig. 2).
- Endogenous ammonium ions are utilized for synthesis of glutamine during antegrade perfusion but are washed out during retrograde perfusion (Exp. 5 and 6).
- Added ammonium ions are mainly converted to urea during antegrade perfusion but are converted to glutamine and urea during retrograde perfusion (Exp. 7 and 8).
- During the inhibition of the competing pathways urea and glutamine synthesis, the

direction of perfusion does not influence the release of glutamine or urea (Exp. 3 and 4, Exp. 9 and 10, Exp. 11 and 12).

- During physiological antegrade perfusion, urea synthesis can remove high ammonia concentrations but is restricted to levels above approximately 0.05 mM (Exp. 3 and 9). The subsequent glutamine synthesis removes very efficiently low ammonia concentrations which were not eliminated by urea synthesis (Exp. 1 and 7). This feature is obtained by the Michaelis-Menten constants with $K_{M,C,NH_4} \gg K_{M,GS,NH_4}$.

Conclusions

Comparisons of these results with a 1-compartment model show that this simpler model is structurally unable to cover the observations made during the perfusion experiments. That means, the 1-compartment model (even if including the same metabolic reactions as the 2-compartment model) can not be fitted to the measurement data with an acceptable modelling error. Consequently, an adequate liver model of glutamine and ammonia metabolism requires the structural mapping of metabolic zonation. By using expert knowledge and experimental data, a 2-compartment model covering all main observed effects could be developed. This 2-compartment model can be used as a general tool for simulation, e.g. defects in metabolic reactions that decrease the ammonia uptake.

References:

- [1] Gebhardt, R.: Metabolic Zonation of the Liver: Regulation and Implications for Liver Function. *Pharmac. Ther.* 53, 275-354, 1992.
- [2] Braeuning, A., Ittrich C., Köhle, C., Hailfinger, S., Bonin, M., Buchmann, A., Schwarz, M.: Differential Gene Expression in Periportal and Perivenous Mouse Hepatocytes. *FEBS Journal* 273, 5051-5061, 2006.
- [3] Häussinger, D.: Hepatocyte Heterogeneity in Glutamine and Ammonia Metabolism and the Role of an Intercellular Glutamine Cycle during Ureogenesis in Perfused Rat Liver. *Eur. J. Biochem.* 133, 269-275, 1983.
- [4] Sies, H., Häussinger, D.: Hepatic Glutamine and Ammonia Metabolism. In: *Glutamine Metabolism in Mammalian Tissue*. Häussinger, Sies (Eds.) Springer-Verlag Berlin Heidelberg, 1984.
- [5] Schimassek, H., Gerok, W.: Control of the Levels of Free Amino Acids in Plasma by the Liver. *Biochemische Zeitschrift*. 343, 407-415, 1965.

Authors:

Dr Susanne Toepfer¹, Dr Sebastian Zellmer², Dominik Driesch¹, Dirk Woetzel¹,
Dr Reinhard Guthke³, Prof Rolf Gebhardt², Dr Michael Pfaff¹

¹ BioControl Jena GmbH
Wildenbruchstraße 15, D-07745 Jena, Germany
Phone: +49 - 3641 - 527831, Fax: +49 - 3641 - 527832
E-mail: susanne.toepfer@biocontrol-jena.com

² University of Leipzig, Medical Faculty
Johannisallee 30, D-04103 Leipzig, Germany

³ Leibniz Institute of Natural Product Research and Infection Biology V. - Hans Knoell Institute
Beutenbergstr. 11a, D-07745 Jena, Germany